

## CONTROLLERS

Whether you want sophisticated programming or built-in convenience, look no further than the Virtualrain controller VRC. The VRC controller offers a proven track record of quality and dependability. With Virtualrain, you choose the watering schedule that best suits your landscape: day of week, odd/even, second day or 1-31 day intervals. With twelve different start times available, you can program the timer to give your landscape just the right amount of precipitation and meet most city scheduling codes. Perfect for all residential landscapes, Virtualrain gives you ease of use, reliability you can count on, and precision programming you can trust.



### Models

VRC-4i	4 Station Indoor Model
VRC-4	4 Station Outdoor Model
VRC-6i	6 Station Indoor Model
VRC-6	6 Station Outdoor Model
VRC-9i	9 Station Indoor Model
VRC-9	9 Station Outdoor Model
VRC-12i	12 Station Indoor Model
VRC-12	12 Station Outdoor Model

### Dimensions

Indoor Model: 8.25"H x 6.25"W x 2.25"D  
 Outdoor Model: 8.25"H x 6.9"W x 4.3"D

### Operating Specifications

Outdoor Models: 120 VAC transformer with internal junction box  
 Indoor Models: 120 VAC transformer with three prong plug in transformer  
 Station output: 24 VAC .60 Amps  
 Valve Capacity: Two 24VAC solenoids per station with pump start  
 Terminal Strip: Screwless accepts #14, #16, #18, #20 AWG wire  
 Circuit Protection: MOV, Fuse Amp  
 Listings: UL Listed, CSA/CE approved

### Features and Benefits

- Dial Programming
- Easy to program self-prompting display
- Available in 4,6,9, and 12 station indoor and outdoor models.
- Choose from three programs (A, B, or C).
- 365-day calendar for ODD or EVEN day watering with leap-year intelligencethrough the year 2050.
- Programmable by day of week, odd or even days, 1-31 days or interval.
- Programmable station delay from 0-59 sec, 1-9 hr.
- Programmable event day off.
- Water budgeting 50-150%.
- Rain sensor bypass switch.
- Non volatile memory.
- Lightning protection for primary and secondary circuitry.
- Programmable rain or event day delay from 1-99 days.



**INDOOR**

### Specification Guide

Example: **VRC - 6i**

Model	Features			
VRC	4i	4 Station Indoor	9i	9 Station Indoor
	4	4 Station Outdoor	9	9 Station Outdoor
	6i	6 Station Indoor	12i	12 Station Indoor
	6	6 Station Outdoor	12	12 Station Outdoor



**OUTDOOR**

### SCREWLESS COLOR-CODED TERMINAL STRIP

